



MUNICIPAL SERVICE LINE TUBING

CSA  CERTIFIED PE-3608

AWWA C901- NSF/ANSI 14 - NSF / ANSI 61

The Advantages of Trinus Service Line Tubing:

Tested and certified by CSA to B137.1 

Noncorroding: Resists decomposition, tuberculation, oxidation and microbiologically induced corrosion.

Chemical Resistant: Please refer to the Trinus Chemical compatibility chart for specific suitability.

High Pressure: Rated at 200 psi @ 72 Deg. F
The short-term factor of safety is 4 to 1 burst.

Flow Rate: Please review Flow Rate in Trinus Pressure Loss chart.

Sequential Marking: Every two feet.

Short Radius Bends

Any radius bend less than those shown should not be used. A elbow should be used if a shorter radius bend is required.

PIPE SIZE	MIN. RADIUS OF BEND
3/4"	19"
1"	23"
1-1/4"	30"
1-1/2"	34"
2"	44"

PRODUCT CODE	NOMINAL SIZE	NOMINAL WALL	NOMINAL I.D	NOMINAL O.D	WEIGHT PER 100 FT (LBS)	LENGTHS (FT)
26101	3/4"	0.102	0.671	0.875	10	100 / 200 / 300 / 500 / 1000
26107	1"	0.131	0.863	1.125	17	100 / 200 / 300 / 500 / 1000
26111	1 1/4"	0.160	1.055	1.375	25	100 / 200 / 300 / 500 / 1000
26114	1 1/2"	0.190	1.245	1.625	36	100 / 200 / 300 / 500 / 1000
26117	2"	0.248	1.629	2.125	58	100 / 200 / 300 / 500 / 1000